

MVH METAL SERIES / 292mm

EN 1822 EFFICIENCY: E10-H14
 MEDIA : Micro Glass Fibre
 SEPARATORS: Hotmelt
 GASKET: Two component continuous, polyurethane
 FINAL PRESSURE DROP: 600 Pascals
 OPERATING TEMPERATURE: 80 °C degrees



HIGH CAPACITY HEPA FILTERS WITH GALVANIZED STEEL FRAME

Part Number	Filter Class (EN 1822)	Width (mm)	Height (mm)	Depth (mm)	Media Area (m ²)	Air Flow (m ³ /h)	Pressure drop (Pascals)
E10							
MVH-305/305/292-10GD	E10	305	305	292	9	1250	250
MVH-305/610/292-10GD	E10	305	610	292	17,5	2500	250
MVH-457/610/292-10GD	E10	457	610	292	26	3750	250
MVH-610/610/292-10GD	E10	610	610	292	35	5000	250
E11							
MVH-305/305/292-11GD	E11	305	305	292	9	1175	250
MVH-305/610/292-11GD	E11	305	610	292	17,5	2350	250
MVH-457/610/292-11GD	E11	457	610	292	26	3520	250
MVH-610/610/292-11GD	E11	610	610	292	35	4700	250
E12							
MVH-305/305/292-12GD	E12	305	305	292	9	900	250
MVH-305/610/292-12GD	E12	305	610	292	17,5	1800	250
MVH-457/610/292-12GD	E12	457	610	292	26	2700	250
MVH-610/610/292-12GD	E12	610	610	292	35	3600	250
H13							
MVH-305/305/292-13GD	H13	305	305	292	9	850	250
MVH-305/610/292-13GD	H13	305	610	292	17,5	1700	250
MVH-457/610/292-13GD	H13	457	610	292	26	2550	250
MVH-610/610/292-13GD	H13	610	610	292	35	3400	250
H14							
MVH-305/305/292-14GD	H14	305	305	292	9	700	250
MVH-305/610/292-14GD	H14	305	610	292	17,5	1400	250
MVH-457/610/292-14GD	H14	457	610	292	26	2100	250
MVH-610/610/292-14GD	H14	610	610	292	35	2800	250