

MVH METAL SERIES / 292mm (MAX. FLOW)

EN 1822 EFFICIENCY: E10-H14
 MEDIA : Micro Glass Fibre
 SEPARATORS: Hotmelt
 GASKET: Two component continuous, polyurethane
 FINAL PRESSURE DROP: 600 Pascals
 OPERATING TEMPERATURE: 80 °C degrees



HIGH CAPACITY HEPA FILTERS WITH GALVANIZED STEEL FRAME

Part Number	Filter Class (EN 1822)	Width (mm)	Height (mm)	Depth (mm)	Media Area (m ²)	Air Flow (m ³ /h)	Pressure drop (Pascals)
E10							
MVH-305/305/292-10GD-10M2	E10	305	305	292	10	1375	250
MVH-305/610/292-10GD-20M2	E10	305	610	292	20	2750	250
MVH-457/610/292-10GD-30M2	E10	457	610	292	30	4120	250
MVH-610/610/292-10GD-40M2	E10	610	610	292	40	5500	250
E11							
MVH-305/305/292-11GD-10M2	E11	305	305	292	10	1250	250
MVH-305/610/292-11GD-20M2	E11	305	610	292	20	2500	250
MVH-457/610/292-11GD-30M2	E11	457	610	292	30	3750	250
MVH-610/610/292-11GD-40M2	E11	610	610	292	40	5000	250
E12							
MVH-305/305/292-12GD-10M2	E12	305	305	292	10	1000	250
MVH-305/610/292-12GD-20M2	E12	305	610	292	20	2000	250
MVH-457/610/292-12GD-30M2	E12	457	610	292	30	3000	250
MVH-610/610/292-12GD-40M2	E12	610	610	292	40	4000	250
H13							
MVH-305/305/292-13GD-10M2	H13	305	305	292	10	1000	280
MVH-305/610/292-13GD-20M2	H13	305	610	292	20	2000	280
MVH-457/610/292-13GD-30M2	H13	457	610	292	30	3000	280
MVH-610/610/292-13GD-40M2	H13	610	610	292	40	4000	280
H14							
MVH-305/305/292-14GD-10M2	H14	305	305	292	10	800	280
MVH-305/610/292-14GD-20M2	H14	305	610	292	20	1600	280
MVH-457/610/292-14GD-30M2	H14	457	610	292	30	2400	280
MVH-610/610/292-14GD-40M2	H14	610	610	292	40	3200	280